

WATER COOLED CONDENSING UNIT


Model: RWUL-B020Y-11R



DATA SHEET


DIMENSIONS TABLE

A	675 mm
B	300 mm
C	194 mm
D	484mm
E	79 mm
F	333 mm




CONNECTIONS & WEIGHT


Water Inlet	G 1"
Water Outlet	G 1"
Liquid Refrigerant Outlet	1/2"
Bolt Size	M10
Weight	71 kg



CONDENSER SPECIFICATION



COMPRESSOR SPECIFICATION



CONDENSER MODEL: 11R


Tube Side	
Volume	1.2 L
Max Allowable Pressure	16 bar
Water flow rate	0.9 m ³ /h
Pressure drop	2.4 kPa
Shell Side	
Volume	4.0 L
Max Allowable Pressure	30 bar

BITZER COMPRESSOR MODEL: 2FES-2Y-40S

Displacement (1450 RPM 50Hz)	9.54 m ³ /h
Max. pressure (LP/HP)	19 / 32 bar
Connection suction line	16 mm – 5/8"
Connection discharge line	12 mm – 1/2"
Motor version	2
Motor voltage	380-420V Y-3-50Hz
Max. Operating current	5.3 A
Max. Power input	2.9 kW
Oil Type	BSE32 (Standard)

The **rime Water-Cooled Condensing Unit** is engineered for reliable, high-efficiency performance in commercial and industrial refrigeration applications. Designed with a compact layout and built using quality-driven components, the unit ensures stable operation, effective

heat rejection, and long-term durability under demanding conditions. Our manufacturing capabilities, reflects a commitment to precision, reliability, and building refrigeration solutions that are designed to perform and built to endure.



CONTACT
SALES@RIMEGROUP.COM
+971 4 4918522

RIME GROUP FZE
Plot No. S21315, South Zone JAFZA, Dubai, UAE
P.O Box 26828 | www.rimegroup.com