rime

WATER COOLED CONDENSING UNIT

Model: RWUL-B040Y-20R

DATA SHEET

DIMENSIONS TABLE

A	890 mm
B	400 mm
C	244 mm
D	622 mm
E	117 mm
F	410 mm



CONNECTIONS & WEIGHT

Water Inlet	G 1"
Water Outlet	G 1"
Liquid Refrigerant Outlet	5/8"
Bolt Size	M12
Weight	132 kg



CONDENSER SPECIFICATION



COMPRESSOR SPECIFICATION



CONDENSER MODEL: 20R

Tube Side	
Volume	2.8 L
Max Allowable Pressure	16 bar
Water flow rate	2.2 m^3/h
Pressure drop	7.9 kPa

Shell Side	
Volume	7.5 L
Max Allowable Pressure	30 bar

BITZER COMPRESSOR MODEL: 4EES-4Y-40S

Displacement (1450 RPM 50Hz)	22.72 m^3/h
Max. pressure (LP/HP)	19 / 32 bar
Connection suction line	28 mm – 11/8"
Connection discharge line	16 mm – 5/8"
Motor version	2
Motor voltage	380-420V Y-3-50Hz
Max. Operating current	12.2 A
Max. Power input	6.9 kW
Oil Type	BSE32 (Standard)

The rime Water-Cooled Condensing Unit is engineered for reliable, high-efficiency performance in commercial and industrial refrigeration applications. Designed with a compact layout and built using quality-driven components, the unit ensures stable operation, effective heat rejection, and long-term durability under demanding conditions. Our manufacturing capabilities, reflects a commitment to precision, reliability, and building refrigeration solutions that are designed to perform and built to endure.

CONTACT
SALES@RIMEGROUP.COM
+971 4 4918522

RIME GROUP FZE
Plot No. S21315, South Zone JAFZA, Dubai, UAE
P.O Box 26828 | www.rimegroup.com